



1. Scrap Collection Device
2. Powerful Brushless Motor
3. 4 Station Electric Automatic Tool Turret
4. Power Socket for Computer & MPG Socket

**Specification:**

Swing over bed	:	200mm (7.9")
Swing over carriage	:	100mm (4")
Center distance	:	460mm (14")
Bed width	:	100mm (4")
Spindle speed	:	100-3000 rpm
Spindle taper	:	Mt3#
Max. Moving Speed of X/Z Axes	:	2m/min
X/Z axes feeding speed	:	500mm/min
Z axes max. travel	:	250mm(13")
X axes max. travel	:	150mm(7")
X/Z axes motor	:	1.35Nm
Tool turret	:	4 Station
Tool turret angle	:	360 degree
Tailstock taper	:	Mt2#
Tailstock travel	:	50mm (2")
Positioning precision	:	0.015mm
Repeat positioning precision	:	0.01mm
Turret return orientation precision	:	0.005mm
Main motor power	:	500w
Machine size (LxWxH)	:	1000X780X565 mm
Packing size (LxWxH)	:	1200x940x770mm
G.W/ N.W.	:	180/140 kg

*As a continuing policy of product improvement at ENKAY Enterprises, the design and specifications are subject to change without prior notice.*



**Manufactured by:**

**ENKAY ENTERPRISES**

605, Padma Tower II, 22, Rajendra Place, New Delhi-110008 (INDIA)

Tel : +91-11-41539634, 25864447 Fax : +91-11-41539633

Email: [info@enkaymachine.com](mailto:info@enkaymachine.com) Web : [www.enkaymachine.com](http://www.enkaymachine.com)