



1. Brushless Motor 500W
2. 4th Axes Driver & Connection
3. One Shot Lubrication Oil Pump
4. Power Socket for Computer and MPG

Specifications :

Drilling Capacity	: 10mm (3/8")
Worktable Size	: 400x145mm (16" x 5.7")
Worktable T-Slot Size	: 8mm (0.31")
No. of T-Slot on Table	: 3
Max. Loading of Worktable	: 20 kg
Table Travel x axes	: 260mm (10")
Table Travel y axes	: 110mm (4.3")
Table Travel z axes	: 180mm (7")
X Axes Feeding Motor Power	: 1.35Nm
Y Axes Feeding Motor Power	: 1.35Nm
Z Axes Feeding Motor Power	: 2.2Nm
X/ Y/ Z Axes Max. Moving Speed	: 2m/min
X/ Y/ Z Axes Feeding Speed	: 500mm/min
Throat	: 150mm (5.9")
Position Precision	: 0.015mm
Repeat Positioning Precision	: 001mm
Spindle Taper	: MT2#
Spindle Speed	: 100-7000rpm
Spindle Motor	: 500w
Machine Size (LxWxH)	: 1040 x 860 x 940 mm
Packing Size (LxWxH)	: 1170 x 960 x 1100 mm
G.W./N.W.	: 218/178 kg

As a continuing policy of product improvement at ENKAY Enterprises, the design and specifications are subject to change without prior notice.



Manufactured by:

ENKAY ENTERPRISES

605, Padma Tower II, 22, Rajendra Place, New Delhi-110008 (INDIA)

Tel : +91-11-41539634, 25864447 Fax : +91-11-41539633

Email: info@enkaymachine.com Web : www.enkaymachine.com